

Φίλτρο Σειράς "F78TS" με φλάντζα

για βιομηχανικές εφαρμογές

F78TS

Φίλτρο για νερό με φλάντζα PN16

- Σώμα από χυτοσίδηρο
- Tmax 40°C (60°C για Pmax 6bar)
- Αυτοκαθαριζόμενο
- 1,5 bar - 16 bar
- Σύμφωνα με EN 13443-1



Τύπος

Τιμές €

F78TS-65FA	100	μm	-	DN = 65	-	Kvs = 69	2405,00
F78TS-65FB	20	μm	-	DN = 65	-	Kvs = 69	2405,00
F78TS-65FC	50	μm	-	DN = 65	-	Kvs = 69	2405,00
F78TS-65FD	200	μm	-	DN = 65	-	Kvs = 69	2405,00
F78TS-80FA	100	μm	-	DN = 80	-	Kvs = 113	3070,00
F78TS-80FB	20	μm	-	DN = 80	-	Kvs = 113	3070,00
F78TS-80FC	50	μm	-	DN = 80	-	Kvs = 113	3070,00
F78TS-80FD	200	μm	-	DN = 80	-	Kvs = 113	3070,00
F78TS-100FA	100	μm	-	DN = 100	-	Kvs = 145	3550,00
F78TS-100FB	20	μm	-	DN = 100	-	Kvs = 145	3550,00
F78TS-100FC	50	μm	-	DN = 100	-	Kvs = 145	3550,00
F78TS-100FD	200	μm	-	DN = 100	-	Kvs = 145	3550,00
EXF125-A	φλάντζα DN100 - DN125						438,00

Τυπική Εφαρμογή για φίλτρο νερού

